TexTest
Fabrics • Apparel • Home Furnishings
Textile Testing Laboratory
3202 34th Street, Valley, AL 36854 Phone: (334)768-1260 or (800)554-7424 Fax: (334)768-1255
Email: alightholder@johnstontextiles.com

TEST REQUEST FORM

CLIENT: _____ DATE SUBMITTED: _____
ADDRESS: _____
_____ [ ] EMAIL REPORT [ ] FAX REPORT
ATTENTION: _____ EMAIL ADDRESS: _____
PHONE: _____
FAX: _____ [ ] RETURN SAMPLES
ORDER#/PO#: _____
CHARGES AUTHORIZED BY: _____

SAMPLE DESCRIPTION

Sample 1 _____ Sample 3 _____
Sample 2 _____ Sample 4 _____

PLEASE CHECK ALL TESTS REQUIRED

DIMENSIONAL STABILITY

___ Shrinkage
___ Machine Wash ____ Hand Wash ____ Commercial Wash ____ Dry Clean

___ 1 Wash
___ 1 & 3 Washes
___ 3 Washes
___ 1 & 5 Washes
___ 5 Washes
___ Follow Care Label

___ Cold (80°F)
___ Warm (105°F)
___ Hot (120°F)
___ Very Hot (140°F)
___ Other _____

___ Flat Dry
___ Drip Dry
___ Line Dry
___ Flat Bed Press
___ Tumble Dry
____Delicate ____Cotton/ Sturdy ____Permanent Press

___ Care Label Determination
___ General Appearance
___ Durable Press Appearance

COLORFASTNESS

___ Laundering AATCC 61
___1A ___2A ___3A ___4A ___5A
___ Bleach/Non-bleach AATCC
___ Crocking AATCC 8
___ Light AATCC 16
__10 Hr. __20 Hr. __40 Hr. ____ Other
___ Perspiration AATCC 15
___ Dry Cleaning Commercial
___ Pool Water AATCC 162
___ Sea Water AATCC 106
___ Water AATCC 107
___ Solvent AATCC 107 Mod.
___ Dry Heat AATCC 117
___ Hot Pressing AATCC 133
___ Ozone AATCC 109
___ Gas Fumes AATCC 23
___ Dye Transfer in Storage AATCC 163

FLAMMABILITY

___ Wearing Apparel 16 CFR 1610
___ Test 1 NFPA 701
___ Test 2 NFPA 701
___ Tentage Floor/Wall CPAI-84 Sec. 6/7
___ Vertical ASTMD6413
___ CAL 117 Section E
___ UFAC Fabric Class
___ Children's Sleepwear 16 CFR 1615/1616

CONSTRUCTION/COMPOSITION ANALYSIS

___ End & Pick Count ASTMD3775
___ Weight ASTMD3776
___Oz/SqYd. ___Oz/LinYd. ___g/M²
___ Width ASTMD3774
___ Yarn Size ASTMD1059
___ Yarn Twist ASTMD1422/1423
___ Thickness ASTMD1777
___ Yarn Type TexTesT
___ Weave/Knit Type TexTesT
___ Air Permeability ASTMD737
___ pH Water Extract AATCC 81
___ Free Formaldehyde AATCC 112
___ % Fiber Content AATCC 20A

WATER/OIL

___ Spray Test AATCC 22
___ Rain Test AATCC 35
___2 mins.@600mm _____ Other
___ Hydrostatic (Low) AATCC 127
___ Hydrostatic (High) ASTMD751
___ Impact Penetration AATCC 42
___ Water Vapor Trans. ASTME96
____Meth B ____Meth BW
___ Wicking ASTMD1117
___ Oil Repellency AATCC118
___ Soil Release AATCC130

STRENGTH

___ Grab Break ASTMD5034
___ Ravel Strip Break ASTMD5035
___ Ball Burst ASTMD3787
___ Mullen Burst ASTMD3786
___ Elmendorf Tear ASTMD1424
___ Trap Tear ASTMD5587
___ Tongue Tear ASTMD2261
___ Seam Slippage ASTMD434/4034
___ Seam Breaks ASTMD1683
___ Dynamic Fatigue Slippage ASTMD4033
___ Stretch ASTMD3107/2594
___ Stretch & Set SAEJ855
___ Peel Adhesion ASTMD751
___ Tension Test 16CFR1500
___ Coefficient of Friction ASTMD1894

ABRASION/PILLING

___ Flex Abrasion ASTMD3885
___ Inflated Diaphragm ASTMD3886
___ Taber Abrasion ASTMD3884
___ Wyzenbeek Abrasion ASTMD4157
___ Martindale Abrasion ASTMD4966
___ Random Tumble Pilling ASTMD3512
___ Martindale Pilling ASTMD4970
___ Brush Pilling ASTMD3511

ADDITIONAL INSTRUCTIONS